

## CLAIMS

- Subs  
a1
1. A method for generating data for a data network with a telecommunications switch, the method comprising the steps of:
- A) receiving a telephone call;
  - B) determining whether the telephone call includes a first data transmission conforming to a predetermined data protocol, the first data transmission including a first digital information signal;
- 5 if the telephone call includes the first data transmission conforming to the predetermined data protocol, then:
- C) terminating the predetermined data protocol; and
  - D) demodulating the first digital information signal from the first data transmission.
- 10
2. The method of claim 1 further comprising the step of:
- E) generating a transmit packet that includes the first digital information signal.
3. The method of claim 3 further comprising the step of:
- F) transmitting the transmit packet into the data network.
4. The method of claim 2 wherein the telecommunications switch only generates the transmit packet when the first data transmission includes the first digital information signal.
- Subs  
a1
5. The method of claim 1 further comprising the steps of:
- E) receiving a receive packet from a data network, the receive packet including a second digital information signal;
  - F) modulating the second digital information signal into a second data transmission conforming to the predetermined data protocol; and
  - G) transmitting the second data transmission in the telephone call.
- 5

6. The method of claim 1 wherein, if the telephone call does not include the first data transmission conforming to the predetermined data protocol, then the telecommunications switch transferring the telephone call to a telephone network.

7. The method of claim 1 wherein a digital signal processor analyzes the telephone call to determine whether the first data transmission conforms to the predetermined data protocol.

8. The method of claim 1 wherein the predetermined data protocol is one of a modem and a facsimile protocol.

9. The method of claim 1 wherein the step of determining whether the telephone call is the first data transmission comprises determining whether one of a called number and calling number for the telephone call is a predetermined number indicating a data call.

10. The method of claim 1 further comprising the steps of:  
if the telephone call includes the first data transmission conforming to the predetermined data protocol, then:

E) translating a called number for the telephone call into a data network  
5 indicator; and

F) establishing a first data connection to a data network based on the data network indicator.

11. The method of claim 10 further comprising the step of:

G) generating a transmit packet that includes the first digital information signal.

12. The method of claim 11 further comprising the step of:

H) transmitting the transmit packet into the data network.

13. The method of claim 10 further comprising the steps of:

G) receiving a receive packet from the data network, the receive packet including a second digital information signal;

H) modulating the second digital information signal into a second data transmission conforming to the predetermined data protocol;

I) transmitting the second data transmission in the telephone call.

14. A telecommunications switching system comprising:

an access circuit that receives telephone calls;

a data protocol analyzer coupled to the access circuit to determine whether telephone calls received from the access circuit include a first data transmission conforming to a predetermined data protocol, the first data transmission including a first digital information signal;

a data protocol terminator coupled to the access circuit to terminate the predetermined data protocol; and

a demodulator coupled to the access circuit to demodulate the first digital information signal from the first data transmission.

15. The system of claim 14 further comprising a data network interface coupled to the demodulator that generates a transmit packet that includes the first digital information signal.

16. The system of claim 15 wherein the data network interface receives a receive packet from a data network coupled to the data network interface, the receive packet including a second digital information signal.

17. The system of claim 16 further comprising:

a modulator coupled to the data network interface that generates a second data transmission conforming to the predetermined data protocol, the second data transmission including the second digital information signal.